




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. . Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

80% depth of discharge cycles EnerSys World	400 EnerSys EMEA
Self-discharge per month at 104°F (40°C)	5%
Self-discharge per month at 68°F (20°C)	1.25%
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Float Charge Voltage	13.5 - 13.8V @ 25°C
Cyclic Charge Voltage	14.4 - 14.8V @ 25°C

Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837

EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland

No. 85, Tuas Avenue 1 Singapore 639518 Tel: +65 6558 7333

© 2024 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E.

Technical Data Sheet correct at time of exporting PDF. Please check website for updates.

ODS-AGM20L

Battery Type

- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle lise

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	675A
Cold Cranking Amps (CCA)	275A
HCA	400A
MCA	350A
20Hr Nominal Capacity (Ah)	18Ah
10Hr Nominal Capacity (Ah)	17Ah
Reserve Capacity Minutes	24 mins
Terminal	M6 Receptacle
Torque Spec in-lbs (Nm max)	50 (5.6)
Recommended Min. Charging Current (A)	1.7A
UPC	635241142365

Dimensions and Weight

_ength	6.9 in / 175 mm
Width	3.4 in / 86 mm
Height (terminals included)	6.1 in / 155 mm
Height (container)	6.1 in / 155 mm
Weight	13 lbs / 5.9 kg

Temperature

L V

V

Operating temperature range -40° F / -40° C to 140° F / $+60^{\circ}$ C Optimum storage temperature 68°F/+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



Want more info? Scan code to access the ODYSSEY® Battery Literature Library



www.odysseybattery.com www.enersys.com

PDF Generated at https://eu.odysseybattery.com 10/02/2024 14:43:30